

Gyproc Jointing Materials

Safety Data Sheet

Health & Safety

1. Identification of the substances / preparation and company

1.1 Product Identifier

Gyproc Joint Filler Gyproc Easi-Fill
Gyproc Cove Adhesive Gyproc Easi-Fill 45

1.2 Relevant identified uses of the substance or preparation and uses advised against

General purpose gypsum-based jointing materials for use with British Gypsum dry lining systems.

This information reflects typical values and is not a product specification.

1.3 Details of the supplier of the safety data sheet

Supplier British Gypsum
 East Leake
 Loughborough
 Leicestershire
 LE12 6HX
Telephone 0844 800 1991
Email bgtechnical.enquiries@bpb.com

2. Hazards identification

2.1 Classification of the substance or preparation

This product is **not** classified as dangerous according to EC regulation 1272/2008 and its amendments.

Dust from mixing or sanding may irritate the respiratory system, skin and eyes.

Hazard Statements:

H303 - May be harmful if swallowed
H332 - Harmful if inhaled
H335 - May cause respiratory irritation

Precautionary Statements: P261, P271, P304 + P340, P312, P301 + P330, P305 + P313, P337 + P351, P264, P405, P403 + P233, P270, P280, P285, P501

3. Composition / information on ingredients

General composition: Calcium sulphate hemihydrate and limestone. Natural constituents may include clay, and minor amounts of quartz. Additives may include minor amounts polymer binders and aggregates. Gyproc Easi-Fill and Easi-Fill 45 also contain perlite aggregate.

4. First aid measures

4.1 Description of first aid measures

Eye contact P305 + P313 - If in eyes, get medical advice
 P337 + P351 - If eye irritation persists, rinse cautiously with water for several minutes.

Skin contact P264 - Wash hands thoroughly after handling.

Ingestion P301 + P330 - If swallowed, rinse mouth.

Inhalation

P261 - avoid breathing dust
P304 + P340 - if inhaled, remove victim to fresh air and keep at rest in a position comfortable for breathing
P312 - Call a doctor, if you feel unwell.

General

Get medical attention if any symptoms persist.

5. Fire fighting measures

The product does not pose a fire hazard. However, some packaging materials may burn.

Suitable extinguishing media – water, foam, carbon dioxide or dry powder.

6. Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Avoid creating dust - see Section 8 for recommended personal protective equipment.

Avoid eye contact or prolonged, repeated contact with skin - see Section 2 for hazards identification.

Prevent plasters from contaminating drains.

7. Handling and storage

7.1 Precautions for safe handling

Use – Minimise dust generation when opening bags, mixing or sanding products in poorly ventilated places. Avoid eye contact or prolonged or repeated contact with skin - see Section 8 for recommended personal protective equipment, and Section 2 for hazards identification.

P264 - Wash hands thoroughly after handling
P270 - Do not eat, drink or smoke when handling this product
P271 - Use only outdoors or in a well ventilated area

Manual handling – Supplied in up to 12.5kg bags – use an appropriate lifting technique.

Product weights:

Product	Bag weight kg	Bags per pallet No.	Pallet weight kg	Pallet weight tonnes
Gyproc Joint Filler	12.5	80	1000	1.0
Gyproc Easi-Fill	10	80	800	0.8
Gyproc Easi-Fill 45	10	80	800	0.8
Gyproc Cove Adhesive	5/12.5	200/80	1000	1.0

(NB) All weights are approximate.

Mechanical handling – To avoid potentially overloading a lift truck, it is important that any effect on load centres is considered. The nominal weight of each palletised load is given within the weights table in this section of this document.

Health & Safety (continued)

Storage – Store in dry conditions. All powdered products can settle in transport. To maintain stability, place pallets on firm level ground, and ensure that stacks are both level and vertical. Do not stack more than one lift high.

P403 + P233 - Store in a well ventilated place. Keep container tightly closed

P405 - Store locked up

8. Exposure control / personal protection

8.1 Workplace Exposure Limit

Substance	Total inhalable	Respirable
Calcium Sulphate Hemihydrate	10mg/m ³ 8hr TWA	4mg/m ³ 8hr TWA
Quartz (silica)	-	0.1mg/m ³ 8hr TWA

8.2 Exposure controls

Ensure adequate general ventilation of work areas to keep dust levels as low as possible. Do not eat, drink or smoke during use. Use personal protective equipment that is clean and has been properly maintained – store in a clean place away from the work area.

Personal protection

Eye / face protection - Avoid contact with eyes. Wear Eye protection to *EN166* standard Category 5-K.

Hand protection - Wear suitable protective gloves to prevent prolonged or repeated skin contact. Recommended properties – impervious gloves to *EN374* standard.
P280 - Wear protective gloves.

Body protection - Work clothing worn by personnel should be laundered regularly.

Respiratory protection - Avoid breathing dust
P285 - In case of inadequate ventilation, wear respiratory protection *EN149:2001* – minimum recommended FFP2.

9. Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance Dry powder.

Odour Odourless.

pH As wet mix - neutral.

10. Stability and reactivity

10.1 Reactivity

No data available.

10.2 Chemical stability

This preparation is stable under the recommended handling and storage conditions in section 7.

10.3 Possibility of hazardous reactions

None under normal conditions of use.

10.4 Conditions to avoid

Avoid dust formation.

10.5 Incompatible materials

No specific restrictions regarding incompatible materials.

10.6 Hazardous decomposition products

No data available.

11. Toxicology information

Inhalation Dust may irritate the respiratory system. No known long term effects.

Skin contact Dry powder may cause skin irritation.

Eye contact Dry powder can cause irritation.

Ingestion Small quantities of plaster should not cause any significant reaction or long term effect.

12. Ecological information

Slightly soluble in water, forms a suspension and solidifies.

13. Disposal consideration

13.1 Waste treatment methods

Do not pour into drains or waterways.

Wastes from gypsum products are normally classified as 'non-hazardous' but should not be co-disposed with municipal waste.

P501 - Dispose of contents of containers at an authorised landfill site in accordance with the Waste Management Licensing Regulations. (See Section 16 Other Information).

14. Transport information

Not classified as hazardous for transportation.

15. Regulatory information

Not classified as dangerous according to EC regulation 1272/2008 and its amendments.

16. Other information

H303 - May be harmful if swallowed

H332 - Harmful if Inhaled

H335 - May cause respiratory irritation

Control of Substances Hazardous to Health Regulations
The Manual Handling Operations Regulations
HSE Guidance Note EH40: Workplace Exposure Limits
Gypsum Wastes – Environment Agency Information Sheet
The British Gypsum **White Book**
The British Gypsum **Site Book**
The British Gypsum website: www.british-gypsum.com

Health & Safety (continued)

Note to user: This Safety Data Sheet does not constitute a workplace risk assessment for COSHH.

There are a number of situations where the approach to manual handling of British Gypsum products should be considered. For further guidance, please refer to the Manual Handling Section of the **Site Book**, available to download from www.british-gypsum.com.

Date of previous version: February 2015.

"Gyproc", "Thistle", "Gypframe" and "Glasroc" are all registered trademarks of BPB United Kingdom Limited. "Isover" is a registered trademark of Saint-Gobain Isover and "Artex" is a registered trademark of BPB United Kingdom Limited.

BPB United Kingdom Limited is a limited company registered in England under company number 734396, having its registered office at Saint-Gobain House, Binley Business Park, Coventry, CV3 2TT, UK. BPB United Kingdom Limited trades as British Gypsum for part of its business activities.

British Gypsum reserves the right to revise product specification without notice. The information herein should not be read in isolation as it is meant only as guidance for the user, who should always ensure that they are fully conversant with the products and systems being used and their subsequent installation prior to the commencement of work. For a comprehensive and up-to-date library of information visit the British Gypsum website at: british-gypsum.com. For information about products supplied by Artex Limited or Saint-Gobain Isover please see their respective websites.

"British Gypsum" is a registered trademark of BPB United Kingdom Limited.

Telephone: 0844 800 1991

Fax: 0844 561 8816

Email: bgtechnical.enquiries@bpb.com

Training enquiries: 0844 561 8810

© British Gypsum July 2015 SDS-308-02

british-gypsum.com

